





ALL Profiles/Frames are 21mm thick and extruded from high tensile FURNITURE grade ALUMINIUM. Finishes are descriptive only.

	50/01 mm BOX*	50/08 mm BOX	50/19 mm BOX	50/31 mm BOX	50/43 mm BOX	50/50 mm BOX
						

Clear Anodised	<input checked="" type="checkbox"/>					
Brushed Stainless	<input checked="" type="checkbox"/>					
Champagne Gloss	<input checked="" type="checkbox"/>					
White Gloss	<input checked="" type="checkbox"/>					
Black Gloss	<input checked="" type="checkbox"/>					
Black Matt	<input checked="" type="checkbox"/>					

Inserts** All Inserts are suitable for all profiles except the 50/01. Compatible inserts for 50/01 can be up to 4.5mm in thickness, must be opaque and, if the insert is glass, must have flat polished edges. Inserts for 50/01 are adhesive fixed only. For more information see Insert Specifications.

Handles No handles are required with Full Overlay Touch to Open Hinges. Clear anodised integrated handle are available.

Handle Positioning	Handle holes can be pre-drilled in suitable inserts - the holes align with the centre of the profile/frame. For handles located in inserts, see available Inserts Specifications - must provide drawing of hole positions required.	Handle holes can be drilled through these profiles/frames. For handles located in inserts only, see available Inserts Specifications - must provide drawing of hole positions required.
---------------------------	---	---

Hinged Doors Supplied with recommended number of hinges determined by height, width & weight of the door. (Can be supplied without hinges)

Available Hinges Profiles/Frames are for Cup Hinges - 95°, 155° & 165°. Cup Hinge 35 mm hole centre must be no less than 78mm from the corners of the door.

Hinge Type Supplied with [a] Full Overlay hinges with the option of Touch to Open [No Handle required] or Soft Close. or [b] Half Overlay or Inlay hinges with the option of Soft Close only.

Strut Door HK-XS Supplied with struts and UNSPRUNG hinges to suit width & weight. Minimum internal carcass HEIGHT for strut is 200 mm.

Spring Flap Door HK [TIP-ON available] Supplied with 2 HK spring loaded stays - mount each side of carcass - no Hinges are required. Minimum internal carcass DEPTH for hardware is 278 mm - Minimum internal carcass HEIGHT is 175 mm. Note: mechanism is 35 mm thick.

Microwave Door HL Supplied with 2 HL spring loaded stays with connecting rod - no hinges required. Minimum internal carcass HEIGHT for microwave door is 263 mm. Note: mechanism is 35 mm thick.

Up & Over Door HS Supplied with 2 HS spring loaded stays with connecting rod - no hinges required. Note: mechanism is 35 mm thick.

Lift Up Bi-Fold HF **ORDER by ENTERING OVERALL HEIGHT AND WIDTH DIMENSIONS of the 2 DOORS REQUIRED.** Supplied with 2 HF spring loaded mechanisms. Also, supplied with 2 Clip Top 120° unsprung hinges up to 1200 mm wide. From 1201 mm to 1800 mm wide - 1 extra hinge included. Note: mechanism is 35 mm thick.

Drawer Fronts All profiles/frames are suitable for this application.

Bottom-Running Sliding Doors for Cabinets only **ORDER by ENTERING INTERNAL CARCASS HEIGHT AND WIDTH DIMENSIONS.** Bottom-running Sliding Doors supplied with aluminium top & bottom track. Each door fitted with 2 top guides and 2 bottom runners. Track available in surface mount or recessed options and, also, either clear anodised or white powder coated aluminium finishes.

Overlay Sliding Doors Bi-Fold [1 pair] for Cabinets only **ORDER by ENTERING OVERALL HEIGHT AND WIDTH DIMENSIONS of the 2 DOORS REQUIRED.** Overlay Sliding Bi-fold Doors are supplied with aluminium top track and 1 left or right handed top runner. Also supplied are concealed hinges and diecast folding door hinges - quantity to suit height & weight of doors. Top runner 35 mm hole(s) will be drilled to suit a 2 mm reveal on 16 mm board.

Overlay Sliding Doors Bi-Fold [2 pair] for Cabinets only **ORDER by ENTERING OVERALL HEIGHT AND WIDTH DIMENSIONS of the 4 DOORS REQUIRED.** Overlay Sliding Bi-fold Doors are supplied with aluminium top track and 2 top runners. Also supplied are concealed hinges and diecast folding door hinges - quantity to suit height and weight of doors. Top runner 35 mm hole(s) will be drilled to suit a 2 mm reveal on 16 mm board.

See Alsert Specifications for minimum and maximum door sizes available.

**** See Insert Specifications. Customers can supply insert material - thickness limited to 5 mm for all profiles except 50/01.**

235 Orchard Road, Richlands Q 4077
 PO Box 687, Sumner Park BC Q 4074
 Tel: 1300 560 042 Fax: 1300 560 069
 Email: sales@alsertdoors.com.au
 www.alsertdoors.com.au