



ALL Profiles/Frames are 21mm thick and extruded from high tensile FURNITURE grade ALUMINIUM. Finishes are descriptive only.


25 mm FLAT




30 mm FLAT




35 mm FLAT




40 mm FLAT



30 mm CURVE



40 mm CURVE



Clear Anodised	✓	✓	✓	✓	✓	✓
Brushed Stainless	✓	✗	✗	✓	✗	✗
Champagne Gloss	✗	✗	✗	✓	✗	✗
Inserts **	All Inserts are suitable for flat profiles. For more information see Insert Specifications.					
Handles	No handles are required with Full Overlay Touch to Open Hinges. Alsert Integrated Handles are not compatible with flat profiles.					
Handle Positioning	Profiles/Frames are not suitable for handle holes, but the holes can be pre-drilled in suitable inserts - see available Insert Specifications. A drawing of hole positions required must be supplied.					
Hinged Doors	Supplied with recommended number of hinges determined by height, width & weight of the door. [Can be supplied without hinges]					
Available Hinges	These Profiles/Frames use Blum Clamp-On Frame Hinges - 95° clip-on - NOT suitable for any other hinge type.					
Hinge Type	Supplied with [a] Full Overlay hinges with the option of Touch to Open [No Handle required] or Soft Close. or [b] Half Overlay or Inlay hinges with the option of Soft Close only.					
Gas Strut Door	Supplied with 2 gas struts and UNSPRUNG hinges to suit width. Minimum internal carcass HEIGHT for gas strut is 178 mm. Flat profile/frame assembly kit included.					
Spring Flap Door HK [TIP-ON available]	Supplied with 2 HK spring loaded stays - mount each side of carcass - no Hinges are required. Flat profile/frame assembly kit included. Minimum internal carcass DEPTH for hardware is 278 mm - Minimum internal carcass HEIGHT is 175 mm. Note: mechanism is 35mm thick.					
Microwave Door HL	Supplied with 2 HL spring loaded stays with connecting rod - no hinges required. Flat profile/frame assembly kit included. Minimum internal carcass HEIGHT for microwave door is 263 mm. Note: mechanism is 35mm thick.					
Up & Over Door HS	Supplied with 2 HS spring loaded stays with connecting rod - no hinges required. Flat profile/frame assembly kit included. Note: mechanism is 35mm thick.					
Lift Up Bi-Fold HF	✗	✗	✗	✗	✗	✗
Drawer Fronts	✗	✗	White MDF infill for fixing drawer front.		✗	White MDF infill for fixing drawer front.
Bottom Running Sliding Doors	✗	✗	✗	✗	✗	✗
Overlay Sliding Doors Bi-Fold	✗	✗	✗	✗	✗	✗

See Alsert Specifications for minimum and maximum door sizes available.

**** See Insert Specifications. Customers can supply insert material - thickness limited to 5 mm.**

Alsert Doors offer the widest range of profiles/frames and insert materials available in Australia. All profiles are extruded and anodised in Europe using high tensile furniture grade aluminium with 10 micron anodising which ensures a scratch resistant surface.

235 Orchard Road, Richlands Q 4077
 PO Box 687, Summer Park BC Q 4074
 Tel: 1300 560 042 Fax: 1300 560 069
 Email: sales@alsertdoors.com.au
 www.alsertdoors.com.au

Alsert | DOORS